

TROUBLESHOOTING SLIMLINE AND INSTANT START INSTALLATIONS

LAMP STYLE STARTING VOLTAGE

F40T12/IS	385
F72T8	540
F72T12	475
F96T8 (200mA)	675
F96T8 (265mA)	675
F96T12	565

RAPID START

RAPID START- 430 MA. LAMP TYPE	STARTING VOLTAGE (MINIMUM @ 50 F)		FILAMENT VOLTAGE
	SINGLE LAMP	TWO LAMP	
F14T12	108	157	7.5 - 9.0
F15T8	108	157	7.5 - 9.0
F15T12	108	157	7.5 - 9.0
F20T12	108	157	3.4 - 4.5
F17T8	140	210	3.4 - 4.5
F25T8	170	260	3.4 - 4.5
F25T12	200	256	3.4 - 4.5
F30T12	150	215	3.4 - 4.5
F32T8	200	300	3.4 - 4.5
F40T8	250	385	3.4 - 4.5
FC6T9	150	225	3.4 - 4.5
FC8T9	180		3.4 - 4.5
FC12T9	200		3.4 - 4.5
FC16T9	205		3.4 - 4.5
FC8T9 / FC12T9		230	3.4 - 4.5
FC12T9 / F16T9		230	3.4 - 4.5